

5910 F1160BVM

75 Ohm Coaxial Cable

Drop Cable


PRODUCT DESCRIPTION:

BONDED FOIL, 60% BRAID, PVC JACKET,
0.072" MESSENGER

CENTER CONDUCTOR:

14 AWG COPPER-CLAD STEEL
NOMINAL DIAMETER: 0.064" (1.63 mm)

DIELECTRIC:

GAS EXPANDED POLYETHYLENE
NOMINAL DIAMETER OVER DIELECTRIC: 0.280" (7.11 mm)

SHIELD:

1ST SHIELD: ALUMINUM-POLYPROPYLENE-ALUMINUM
LAMINATED TAPE WITH OVERLAP BONDED
TO THE DIELECTRIC
NOMINAL DIAMETER OVER TAPE: 0.287" (7.29 mm)

2ND SHIELD: 34 AWG ALUMINUM BRAID WIRE
60% COVERAGE

JACKET:

PVC JACKET
NOMINAL DIAMETER OVER JACKET: 0.395" (10.03 mm)
NOMINAL JACKET THICKNESS: 0.042" (1.07 mm)

MESSENGER:

NOMINAL DIAMETER OF MESSENGER: 0.072" (1.83 mm)
MINIMUM BREAKING STRENGTH: 365 lbs. (166 kg)


ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 +/- 3.0 Ohms
VELOCITY OF PROPAGATION: 85.0% NOMINAL
ATTENUATION: @ 68°F (20°C)

Shipping Weight (Lbs.)/1000': 88 lbs.

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.38 dB	1.25 dB
55 MHz	0.96 dB	3.15 dB
83 MHz	1.18 dB	3.87 dB
187 MHz	1.75 dB	5.74 dB
211 MHz	1.90 dB	6.23 dB
250 MHz	2.05 dB	6.72 dB
300 MHz	2.25 dB	7.38 dB
350 MHz	2.42 dB	7.94 dB
400 MHz	2.60 dB	8.53 dB
450 MHz	2.75 dB	9.02 dB
500 MHz	2.90 dB	9.51 dB
550 MHz	3.04 dB	9.97 dB
600 MHz	3.18 dB	10.43 dB
750 MHz	3.65 dB	11.97 dB
865 MHz	3.98 dB	13.05 dB
1000 MHz	4.35 dB	14.27 dB